

GOES-R Rebroadcast (GRB) Simulator Fact Sheet



	Highlights
	2 Transit Cases – Approximately 2'W X 4'L X 4'H stacked together
Physical Features	Total Weight – Approximately 470 lbs
	Each Transit Case contains: Front and Back removable hard covers, 4 side handles, RJ45
	cables, IF cables, USB cables, VGA cables, and power cords
	Transit Case 1 (Top) contains 8-port KVM console, IBM Server, 16-port Network Switch, and Power Distribution Unit
	Transit Case 2 (Bottom) contains Time Code Generator, Dual Channel RT Logic Front End
	Processor, Dual Channel RT Logic Modem, and Power Distribution Unit
	GPS Antenna and cable included
	GF3 Afficilità affic cable filcioded
Downlink Specifications	Input Center Frequency – 1686.6 MHz
	Polarization – Dual Circular: Left-Hand and Right-Hand
	Primary Modulation – 8PSK
	Alternate Modulation - QPSK
	Signal Format – DVB-S2
	Output of the DVB-S2 Demodulator – 15.5 Mbps
	Bandwidth per polarization: 9.8 MHz for Primary Modulation
	10.9 MHz for Alternate Modulation
	Block Length – 64800 bits
Software Features	Provides high-fidelity streams of Consultative Committee for Space Data Systems (CCSDS)
	formatted GRB packet data equivalent to live GRB data
	Simulates Imager (ABI and SUVI) and Non-Imager (GLM, SEISS, EXIS, and MAG) instrument
	data streaming
	Two Modes of Operation:
	 Off-line for setup of configurations, scenarios, test patterns, proxy data, and event
	logs and reports
	On-line for simulation of GRB packet generation
	Graphical User Interface (GUI) allows users to create, modify, view, and delete configurations
	scenarios, test patterns (images), event logs, and reports
	Simulations from GUI are controlled by editable test scenarios
	Scenario scripts specify the test data to use and the series of actions for the GRB Simulator to
	perform when generating output of GRB packet generation
	Test Patterns: Images – Monochromatic and RGB in JPEG or PNG format
	Proxy Data files (L1b data) in netCDF format Non-Images – Sine Wave, Triangular, or Square patterns via scenario scripts

